



ITALCAR INDUSTRIAL S.r.l. – Via Bruino, 36 – 10040 Rivalta di Torino
tel. 011.9040225 – fax 011.9032986
www.italcar.com - info@italcar.com



MODEL SHUTTLE.4

MINIBUS 14 PLACES 72V

TECHNICAL FEATURES – SHUTTLE.4

| | | | |
|------------------------|---|--------------------------------|---|
| MOTOR: | AC 72v | VOLTAGE: | 72 volt |
| BATTERIES: | 18 x 8volt – US battery US8VGC (2 pack, 9x8v, in parallel) | SUSPENSION: | front helical spring and rear leaf spring with hydraulic shock absorber |
| CONTROLLER: | electronic for AC system engines: SEVCON GEN4 550Ah | BODY: | “PP” Alloy automatic industrial special plastic 14 places |
| BRAKES: | Automotive type, double hydraulic circuits on 4 wheels with hand brake * Front: disc * Rear: drum | PERFORMANCES: | * maximum speed: 40 km/h * autonomy: 80 km * hill climbing ability: 10% |
| | | | <small>datas are to be considered indicative and calculated on the average of different conditions of use</small> |
| TRANSMISSION: | rear axle, 19 spline, ratio 12,31:1 | TYRES: | 12 inch aluminium wheel & 6PR tyre |
| DIMENSIONS: | length 5000mm width 1480mm height 1960mm | CHARGER: | nr. 2, mod. 72v/16A |
| TURNING RADIUS: | 5.5 mt | STANDARD CONFIGURATION: | radio CD player, alloy wheels, reverse buzzer, front and rear lights, direction lights, horn, 2 points seat belts |
| | | COLOURS: | white |

All data reported are indicatives and not binding. ITALCAR INDUSTRIAL S.r.l. maintains the right to bring any changes without notice