



attiva 6L.5



48 VOLT WITH AC SYSTEM
8 X 6V LEAD-ACID BATTERIES
205/50-10 ALUMINUM RIMS
FRONT & REAR LIGHTS
HYDRAULIC BRAKES ON 4
WHEELS + HANDBRAKE

ITALCAR INDUSTRIAL SRL | Via Bruino, 36 | 10040 Rivalta di Torino (TO)
Tel. +39 011 9040225 | Fax +39 011 9032986 | info@italcar.com | www.italcar.com



ITALCAR an Italian Brand



attiva 6L.5

places:	6 (4 +2)	
batteries:	8 x 6V, US2200 standard	
motor:	AC 48V – Mahle Letrika	
controller:	sevcon GEN4 – AC – 450A	
transmission:	rear axle, 19 spline, ratio 12,31:1	
steering:	self compensating single reduction rack and pignon	
performances:		
suggested max speed	30 km/h	
range	80 km	
max hill climbing ability	25%	
dimensions:		
overall	3700mm x 1200mm x 1800mm	
ground clearance (empty):	210mm	
turning radius:	4 mt	
wheel base	2400mm	
chassis:	galvanized steel frame and powder coated	
body:	PP impregnated and painted	
suspensions:		
front	Independent suspensions	
rear	leaf springs with hydraulic shock absorbers	
brakes:	automotive types, double hydraulic circuit on four wheel with hand brake	
front	Disc	
rear	drum	
tyres:	205 / 50 – 10 with aluminium rims	
recommended pressure:	1,7 bar (25psi)	
battery charger:	included with the vehicle - 48v, 220/230V	
basic configuration:	Includes: reverse buzzer; digital speedometer, front and rear lights, horn, direction indicators, rear-view mirrors, one piece plexiglass	

All above specification were correct at the time of the printing and are considered indicatives and not binding. ITALCAR INDUSTRIAL S.r.l. maintains the right to bring any changes without notice

clicca mi piace - like us on



segui su - follow us on

