



attiva 8L.5




48 VOLT WITH AC SYSTEM

8 X 6V LEAD-ACID BATTERIES

205/50-10 ALUMINUM RIMS

FRONT & REAR LIGHTS

HYDRAULIC BRAKES ON 4
WHEELS + HANDBRAKE



ITALCAR an Italian Brand

attiva 8L.5

places:	8 (6 +2)
batteries:	8 x 6V, US2200 standard
motor:	AC 48V – Mahle Letrika
controller:	sevcon GEN4 – AC – 450A
transmission:	rear axle, 19 spline, ratio 12,31:1
steering:	self compensating single reduction rack and pignon
performances:	
suggested max speed	30 km/h
range	80 km
max hill climbing ability	25%
dimensions:	
overall	4300mm x 1200mm x 1800mm
ground clearance (empty):	210mm
turning radius:	5,1 mt
wheel base	3200mm
chassis:	galvanized steel frame and powder coated
body:	PP impregnated and painted
suspensions:	
front	Independent suspensions
rear	leaf springs with hydraulic shock absorbers
brakes:	automotive types, double hydraulic circuit on four wheel with hand brake
front	Disc
rear	drum
tyres:	205 / 50 – 10 with aluminium rims
recommended pressure:	1,7 bar (25psi)
battery charger:	included with the vehicle - 48v, 220/230V
basic configuration:	Includes: reverse buzzer; digital speedometer, front and rear lights, horn, direction indicators, rear-view mirrors, one piece plexiglass



clicca mi piace - like us on



segui su - follow us on



All above specification were correct at the time of the printing and are considered indicatives and not binding. ITALCAR INDUSTRIAL S.r.l. maintains the right to bring any changes without notice